



**Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: [info@everbuild.co.uk](mailto:info@everbuild.co.uk)

website: [www.everbuild.co.uk](http://www.everbuild.co.uk)

## CONSTRUCTION PRODUCTS REGULATION

### DECLARATION OF PERFORMANCE

**No: 1121-CPR-JA5018**

|  |   |
|--|---|
| 1. Identification Code                                     | <b>EVERFLEX PYRO MATE</b><br><br><b>Codes: PYROLASTIC</b>   |
| 2. Type, Batch and/or Serial Number                        | <b>- For batch number - see packaging</b>   |
| 3. Intended use  | <b>Fire Stopping and Sealing Product for Linear Joint and Gap Seals, see ETA 13/1059</b>  |
| 4. Manufacturer  | <b>Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW</b>   |
| 5. Authorised Representative                               | <b>Not Applicable</b>   |
| 6. Assessment and Verification of Constancy of Performance | <b>System 1</b>   |
| 7. Notified Body and Tasks                                 | <b>Exova Warringtonfire 1104</b>  |
| 8. European Technical Assessment                           | <b>Exova Warringtonfire issued European Technical Approval ETA 13/1059 on the basis of ETAG 026, edition 2011, used as European Assessment Document (EAD)</b> |
| 9. Declared Performance                                    | <b>TO ETAG 026 Edition 2011</b>   |
| Reaction to Fire   | <b>Class E</b>  |
| Resistance to Fire   | <b>Resistance to fire performance and field application in accordance with En 13501-2. See ETA 13/1059</b>  |



**Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,  
Cross Green Industrial Estate, Leeds, LS9 0SW  
Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424  
Fax: +44 (0) 113 240 0024  
e-mail: info@everbuild.co.uk  
website: www.everbuild.co.uk

|                               |   |
|-------------------------------|---|
| Air Permeability              | <b>Tested according to EN1314-1 see ETA 13/1059</b> |
| Dangerous Substances          | <b>See Clause 2.5</b>                               |
| Airborne sound insulation     | <b>Rw(C;Ctr) = 38 (-2;-9)</b>                       |
| Durability and serviceability | <b>Z<sub>1</sub></b>                                |
| Movement Capability           | <b>According to ISO 11600 F25LM</b>                 |

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9 . The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed: I. G. Southerington – Head of Technical

P.R. Thomas – Technical Manager

Dated: Leeds, 1/4/14