

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** 2 PART WOOD FILLER - RESIN

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC9b: Fillers, putties, plasters, modelling clay.

### 1.3. Details of the supplier of the safety data sheet

**Company name:** EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9OSW

ENGLAND

**Tel:** 0044 113 240 3456

**Fax:** 0044 113 240 0024

**Email:** sds@everbuild.co.uk

### 1.4. Emergency telephone number

**Emergency tel:** 0044 113 240 3456 (office hours only)

**Manufacturer:** EVERBUILD BUILDING PRODUCTS LTD

Site 41

Knowsthorpe Way, Cross Green Industrial Estate

Leeds

West Yorkshire

LS9 0SW

United Kingdom

Tel: (0044) 113 240 3456

Fax: (0044) 113 240 0024

Emergency tel: (0044) 113 240 3456

Email: sds@everbuild.co.uk

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CHIP:** Xn: R48/20; Xn: R63

**Classification under CLP:** Skin Irrit. 2: H315; Eye Irrit. 2: H319; Repr. 2: H361d; STOT RE 1: H372; Flam. Liq. 2: H225; Flam. Liq. 3: H226; Acute Tox. 4: H332

# SAFETY DATA SHEET

## 2 PART WOOD FILLER - RESIN

Page: 2

**Most important adverse effects:** Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
Possible risk of harm to the unborn child.

### 2.2. Label elements

#### Label elements:

**Hazard statements:** H226: Flammable liquid and vapour.  
H372: Causes damage to organs hearing organs through prolonged or repeated exposure.  
H332: Harmful if inhaled.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H361d: Suspected of damaging the unborn child.

**Signal words:** Danger

**Hazard pictograms:** GHS02: Flame  
GHS07: Exclamation mark  
GHS08: Health hazard



**Precautionary statements:** P102: Keep out of reach of children.  
P270: Do not eat, drink or smoke when using this product.  
P202: Do not handle until all safety precautions have been read and understood.  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.  
P264: Wash hands thoroughly after handling.  
P260: Do not breathe vapours.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+352: IF ON SKIN: Wash with plenty of water/soap.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+313: If eye irritation persists: Get medical attention.  
P308+313: IF exposed or concerned: Get medical advice.  
P332+313: If skin irritation occurs: Get medical advice.  
P321: Specific treatment (see information on this label).  
P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P362: Take off contaminated clothing.  
P370+378: In case of fire: Use powder, foam or carbondioxide to extinguish.

#### Label elements under CHIP:

**Hazard symbols:** Harmful.

[cont...]

# SAFETY DATA SHEET

## 2 PART WOOD FILLER - RESIN

Page: 3



**Risk phrases:** R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R63: Possible risk of harm to the unborn child.

**Safety phrases:** S2: Keep out of the reach of children.

S36/37: Wear suitable protective clothing and gloves.

S46: If swallowed, seek medical advice immediately and show this container or label.

### 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive dust-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### STYRENE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
202-851-5	100-42-5	-: R10; Xn: R20; Xi: R36/38; Xn: R48/20; Xn: R63	Flam. Liq. 3: H226; Repr. 2: H361d; Acute Tox. 4: H332; STOT RE 1: H372; Skin Irrit. 2: H315; Eye Irrit. 2: H319	10-30%

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.  
Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Do not induce vomiting. If conscious, give half a litre of water to drink immediately.  
Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

[cont...]

**SAFETY DATA SHEET**  
2 PART WOOD FILLER - RESIN

Page: 4

**4.3. Indication of any immediate medical attention and special treatment needed**

**Immediate / special treatment:** Not applicable.

**Section 5: Fire-fighting measures**

**5.1. Extinguishing media**

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

**5.2. Special hazards arising from the substance or mixture**

**Exposure hazards:** Highly flammable. In combustion emits toxic fumes. May form flammable / explosive dust-air mixture.

**5.3. Advice for fire-fighters**

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**Section 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition.

**6.2. Environmental precautions**

**Environmental precautions:** Do not discharge into drains or rivers.

**6.3. Methods and material for containment and cleaning up**

**Clean-up procedures:** Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

**6.4. Reference to other sections**

**Reference to other sections:** Refer to section 8 of SDS.

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of dust in the air.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

**Suitable packaging:** Must only be kept in original packaging.

**7.3. Specific end use(s)**

**Specific end use(s):** No data available.

[cont...]

**SAFETY DATA SHEET**  
2 PART WOOD FILLER - RESIN

Page: 5

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Hazardous ingredients:**

**STYRENE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	430 mg/m <sup>3</sup>	1080 mg/m <sup>3</sup>	-	-

**DNEL/PNEC Values**

**DNEL / PNEC** No data available.

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Respiratory protective device with particle filter.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Paste

**Colour:** Various

**Odour:** Pungent

**Evaporation rate:** Moderate

**Solubility in water:** Insoluble

**Also soluble in:** Most organic solvents.

**Viscosity:** Highly viscous

**Boiling point/range°C:** >200

**upper:** 6.1

**Autoflammability°C:** 490

**Relative density:** >1.0g/cm<sup>3</sup>

**Flammability limits %: lower:** 1.1

**Flash point°C:** 23 - 55

**Vapour pressure:** 6.52mB at 20`c (sty)

**9.2. Other information**

**Other information:** No data available.

**Section 10: Stability and reactivity**

**10.1. Reactivity**

**Reactivity:** Stable under recommended transport or storage conditions.

[cont...]

**SAFETY DATA SHEET**  
2 PART WOOD FILLER - RESIN

Page: 6

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

**10.3. Possibility of hazardous reactions**

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

**10.4. Conditions to avoid**

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

**10.5. Incompatible materials**

**Materials to avoid:** Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

**Haz. decomp. products:** In combustion emits toxic fumes.

**Section 11: Toxicological information**

**11.1. Information on toxicological effects**

**Hazardous ingredients:**

**STYRENE**

IVN	MUS	LD50	90	mg/kg
ORL	MUS	LD50	316	mg/kg
ORL	RAT	LD50	2650	mg/kg

**Relevant effects for mixture:**

Effect	Route	Basis
Repeated dose toxicity	INH	Hazardous: calculated

**Symptoms / routes of exposure**

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Section 12: Ecological information**

**12.1. Toxicity**

**Ecotoxicity values:** No data available.

**12.2. Persistence and degradability**

**Persistence and degradability:** Biodegradable.

[cont...]

**SAFETY DATA SHEET**  
2 PART WOOD FILLER - RESIN

Page: 7

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** No bioaccumulation potential.

**12.4. Mobility in soil**

**Mobility:** Absorbed only slowly into soil.

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

**12.6. Other adverse effects**

**Other adverse effects:** Negligible ecotoxicity.

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**14.1. UN number**

**UN number:** UN3269

**14.2. UN proper shipping name**

**Shipping name:** POLYESTER RESIN KIT

**14.3. Transport hazard class(es)**

**Transport class:** 3

**14.4. Packing group**

**Packing group:** III

**14.5. Environmental hazards**

**Environmentally hazardous:** No

**Marine pollutant:** No

**14.6. Special precautions for user**

**Special precautions:** No special precautions.

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Specific regulations:** Not applicable.

[cont...]

**SAFETY DATA SHEET**  
2 PART WOOD FILLER - RESIN

Page: 8

**15.2. Chemical Safety Assessment**

**Section 16: Other information**

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H361d: Suspected of damaging the unborn child.

H372: Causes damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

R10: Flammable.

R20: Harmful by inhalation.

R36/38: Irritating to eyes and skin.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R63: Possible risk of harm to the unborn child.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.