

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: LEAD MATE SEALANT

Product code: LEAD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9OSW

ENGLAND

Tel: 0044 113 240 3456

Fax: 0044 113 240 0024

Email: sds@everbuild.co.uk

1.4. Emergency telephone number

Emergency tel: 0044 113 240 3456 (office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; -: EUH208

Most important adverse effects: Contains n-(2-aminoethyl)-3-aminopropyltrimethoxysilane. May produce an allergic reaction. Causes serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains n-(2-aminoethyl)-3-aminopropyltrimethoxysilane. May produce an allergic reaction.

H319: Causes serious eye irritation.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark



SAFETY DATA SHEET

LEAD MATE SEALANT

Page: 2

Precautionary statements: P264: Wash hands thoroughly after handling.
P280: Wear eye protection and gloves.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+313: If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS, C14-C18, N-ALKANES, ISOALKANES, CYCLICS, <2% - REACH registered number(s): 01-2119457736-27-0001

EINECS	CAS	PBT / WEL	CLP Classification	Percent
927-632-8	-	-	Asp. Tox. 1: H304; -: EUH066	10-30%

TRIMETHOXY VINYLSILANE

220-449-8	2768-02-7	-	Acute Tox. 4: H332; Flam. Liq. 3: H226	1-10%
-----------	-----------	---	--	-------

N-(2-AMINOETHYL)-3-AMINOPROPYLTRIMETHOXYSILANE

217-164-6	1760-24-3	-	Eye Dam. 1: H318; Aquatic Chronic 2: H411; Acute Tox. 4: H332; Skin Sens. 1: H317	<1%
-----------	-----------	---	---	-----

METHANOL - REACH registered number(s): 01-2119433307-44-XXXX

200-659-6	67-56-1	-	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370	<1%
-----------	---------	---	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

[cont...]

SAFETY DATA SHEET

LEAD MATE SEALANT

Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

[cont...]

SAFETY DATA SHEET

LEAD MATE SEALANT

Page: 4

Hazardous ingredients:

METHANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	266 mg/m ³	333 mg/m ³	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Grey

Odour: Barely perceptible odour

Viscosity: Highly viscous

Boiling point/range°C: >100

Flash point°C: >93

Relative density: ~1

VOC g/l: 21.1

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

[cont...]

SAFETY DATA SHEET

LEAD MATE SEALANT

Page: 5

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

METHANOL

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

TRIMETHOXY VINYLSILANE

Daphnia magna	-	21D NOEC 28	mg/l
Daphnia magna	48H EC50	169	mg/l
GREEN ALGA (Selenastrum capricornutum)	-	72H NOEC 25	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H IC50	210	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	191	mg/l

N-(2-AMINOETHYL)-3-AMINOPROPYLTRIMETHOXYSILANE

Scenedesmus Subspicatus	72H EC50	126	mg/l
-------------------------	----------	-----	------

[cont...]

SAFETY DATA SHEET

LEAD MATE SEALANT

Page: 6

ZEBRAFISH (Brachydanio rerio)	96H LC50	597	mg/l
-------------------------------	----------	-----	------

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste code number: 08 04 10

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.
EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.
H225: Highly flammable liquid and vapour.
H226: Flammable liquid and vapour.
H301: Toxic if swallowed.
H304: May be fatal if swallowed and enters airways.
H311: Toxic in contact with skin.

[cont...]

SAFETY DATA SHEET

LEAD MATE SEALANT

Page: 7

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H370: Causes damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.